

P400-E36-V2G40

All in one amoured P400, 650tvl, Up to 40m IR Range



General Features

- **CCD: 1/3" SONY**
- **DSP: EFFIO-E**
- **Lens: 2.8-12mm Varifocal**
- **Illumination: 0 Lux (IR LED On)**
- **Res: 650TVL**
- **IR LED: 48pcs**
- **IR Range: Up to 40m**
- **Voltage: 12V DC**

Specification

Image Sensor	1/3" SONY Super 960H EXVIEW HAD CCD
DSP	SONY EFFIO-E
Horizontal Resolution	650TV Line
Lens	2.8-12mm Mega pixel lens
IR Led	48 PCS
IR Range	Up to 40M
Current Consumption	110mA (IR OFF) ,430mA (IR ON)
S/N Ratio	≥52dB (AGC OFF)
Menu	OSD Control
Picture Elements	PAL: 1024 (H) × 596 (V) NTSC: 1028 (H) × 508 (V)
Effective Pixel	PAL: 976 (H) × 582 (V) NTSC: 976 (H) × 494 (V)
Auto Gain Control	AUTO (4 STEP)
White Balance	ATW/PUSH/USER1/USER2/ANTI CR/ MANUAL/PUSH LOCK
Back Light Compensation	BLC & HSBC
Day/Night	Auto/COLOR / B&W
Privacy Masking	ON / OFF (4 Zone)
Motion Detection	ON/OFF(24*16 Zone)
Dynamic Noise Reduction	2D
Language	English/Japanese/Chinese/German/ French/ Russian/Portuguese/Spanish
Scanning System	2:1 Interlace
Min Illumination	0 Lux (IR ON)
Auto Electronic Shutter	PAL:1/50-1/100,000S , NTSC:1/60-1/100,000S
Video output	1Vp-p,75Ω
Gamma Correction	0
Power Supply	DC12V±20%
IP Rating	IP65
Storage Temperature	-20°C+60°C
Operating Temperature	-10°C+50°C
Dimensions	240*105*200mm
Weight	1210g

Dimensions

