

MINI-PTZ-EXT

- Amazingly small and powerful PTZ
 - Perfect to swap a camera to PTZ
 - RS485 or Coaxial transmission option*
 - High Resolution
 - Day/Night Operation
 - Full OSD Menu
 - Built-In Samsung Module 100x Zoom (10 x Optical, 10 x Digital)
 - Pan 360° continuous with slip ring, Tilt 0°-90° with auto-flip
 - 128 Presets with titles editable; pan/tilt, lens positions, and zoom adjustable
 - Auto scan, 4 pattern tours, 1 cruise tour
- *Coaxitron transmission up to 200 metres



Specification

Camera

Pick-Up Device:	Samsung 1/4" Interline Transfer CCD
Resolution:	500TVL 9Day) – 570TVK (Night)
Min. Illumination:	0.7Lux – 0.02Lux
Lens:	3.8-38mm – F1.8
Angle of View Horiz.	51.2° (Wide) ~ 5.58°(tele)
Angle of View Vertical:	39.3° (Wide) ~ 4.27° (tele)
White Balance:	Auto / Manual
Gain Control:	Auto Gain Control

PTZ Functions

Digital Shutter:	Auto: 1/50-1/120,000s
Zoom:	10 x Optical, 10 x Digital
Pan Rotation Speed:	0.5° - 160°/sec (360° continuously)
Tilt Rotation Speed:	0.5° - 90°/sec with auto flip
Preset:	128
Baud Rate:	Pelco 2400/4800/9600/19200 bps

Electrical/Environmental

S/N Ratio:	More than 50db
Power Supply:	Regulated 12V DC
Consumption:	1.5A (9w)
Environment Humidity:	0-95% (No Condensation)
Operation Temperature:	-10°C ~ +50°C

Physical

Dimensions:	152mm (d) x 177.6mm (h)
Weight:	Approx 2.5kg